

Cooling Units

Pfannenberg

Door or Side Mounting Cooling Units

Reference No	Dimensions H x W x D (mm)	Cooling Capacity at A35/A35* (W)	Voltage (V _{AC})	Freq. (Hz)
CLDTS 9031	565 x 310 x 212	510	115 / 230	50 / 60
CLDTS 9041	604 x 380 x 231	870	115 / 230	50 / 60
CLDTS 9141	964 x 410 x 248	950	115 / 230 / 400	50 / 60
CLDTS 9241	1539 x 485 x 180	1000	230 / 400	50 / 60
CLDTS 9341	1539 x 485 x 180	1500	230 / 400	50 / 60
CLDTS 9341C	964 x 410 x 248	1550	230 / 400	50 / 60
CLDTS 9441	1543 x 485 x 240	2000	400	50 / 60
CLDTS 9541	1543 x 485 x 240	2500	400	50 / 60
CLDTS 9841	1549 x 485 x 360	4000	400	50 / 60



Outdoor Cooling Units (IP 56)

Reference No	Dimensions H x W x D (mm)	Cooling Capacity at A35/A35* (W)	Voltage (V _{AC})	Freq. (Hz)
CLDTS 3161	748 x 395 x 294	1100	115 / 230 / 400	50 / 60
CLDTS 3261	1209 x 395 x 326	2000	115 / 230 / 400	50 / 60

Ex-Proof Cooling Units (IP 65)

Reference No	Dimensions H x W x D (mm)	Cooling Capacity at A35/A35* (W)	Voltage (V _{AC})	Freq. (Hz)
CLDTS-Ex7541	1804 x 475 x 451	2450	230	50 / 60

Partially Recessed Door or Side Mounting Cooling Units

Reference No	Dimensions H x W x D (mm)	Installation Depth (mm)	Cooling Capacity at A35/A35* (W)	Voltage (V _{AC})	Freq. (Hz)
CLDTI 9021	329 x 385 x 252	74	300	115 / 230	50 / 60
CLDTFI9021	326 x 385 x 252	177	300	115 / 230	50 / 60
CLDTI 9031	562 x 310 x 212	67	510	115 / 230	50 / 60
CLDTI 9041	599 x 380 x 231	60	870	115 / 230	50 / 60
CLDTI 9141	958 x 410 x 248	82	950	115 / 230 / 400	50 / 60
CLDTI 9241	1536 x 485 x 180	60	1000	230 / 400	50 / 60
CLDTI 9341	1536 x 485 x 180	60	1500	230 / 400	50 / 60
CLDTI 9341C	958 x 410 x 248	82	1500	230	50 / 60
CLDTI 9441	1536 x 485 x 240	120	2000	400	50 / 60
CLDTI 9541	1536 x 485 x 240	120	2500	400	50 / 60
CLDTI 9841	1536 x 485 x 360	120	4000	400	50 / 60

Roof Mounting Cooling Units

Reference No	Dimensions H x W x D (mm)	Cooling Capacity at A35/A35* (W)	Voltage (V _{AC})	Freq. (Hz)	Noise Level dB(A)
CLDTD 5101	405 x 600 x 390	810	115 / 230	50 / 60	63
CLDTD 5201	405 x 600 x 390	1150	115 / 230	50 / 60	72
CLDTD 5301	405 x 600 x 390	1400	115	50 / 60	72
CLDTD 5301	405 x 600 x 390	1600	230	50 / 60	72
CLDTD 5301	405 x 600 x 390	1700	400	50 / 60	72
CLDTD 5501	475 x 720 x 465	3000	400	50 / 60	75



* In accordance with EN 814: At 35°C ambient temperature and 35°C temperature inside switch cabinet.